1.85mm Male to G3PO (SMPS) Female Cable Assembly, RG-405SS Flexible Coax Cable, DC–67 GHz

Coaxial cable assembly · DC–67 GHz · 1.85mm / G3PO male / female · 9 lengths, 100 mm to 1000 mm



Overview

1.85mm Male to G3PO (SMPS) Female Cable Assembly, rated DC–67 GHz. Available in 9 lengths from 100 mm to 1000 mm, listed below. All figures are the maker's datasheet values. Ships from US stock.

Applications

- Connecting instruments, modules and antennas
- Test-bench and lab wiring
- Integration in RF and radar test setups

Specifications

Frequency	DC–67 GHz
Impedance	50 Ω
Connector 1	1.85 mm male straight; stainless steel, passivated
Connector 2	G3PO female straight; beryllium copper, gold
VSWR / return loss	10 dB to 67 GHz
RF leakage	100 dB
Cable type	Flexible
Cable outer diameter	2.64 mm
Mating cycles, min	≥500
Operating temperature	−45 °C to +125 °C
RoHS	Yes
Inner conductor material	Silver Plated Copper Wire
Dielectric material	PTFE
Jacket material	FEP

Cable color	Turquoise
Minimum bend radius	6 mm
Capacitance (pF/m)	96.5
Velocity of propagation	70%
Shielding effectiveness	< −100 dB @ 1 GHz

Options (Length)

100 mm · SKU KYM-US-CBL-0051-100

Insertion loss	≤ 1.79 dB at 67 GHz
Length tolerance	±3 mm

150 mm · SKU KYM-US-CBL-0051-150

200 mm · SKU KYM-US-CBL-0051-200

Insertion loss	≤ 2.55 dB at 67 GHz
Length tolerance	±3 mm

250 mm · SKU KYM-US-CBL-0051-250

300 mm · SKU KYM-US-CBL-0051-300

Insertion loss	≤ 3.32 dB at 67 GHz
Length tolerance	±3 mm

400 mm · SKU KYM-US-CBL-0051-400

500 mm · SKU KYM-US-CBL-0051-500

Insertion loss	≤ 4.85 dB at 67 GHz
Length tolerance	±5 mm

800 mm · SKU KYM-US-CBL-0051-800

Insertion loss	≤ 7.18 dB at 67 GHz
Length tolerance	±5 mm

1000 mm · SKU KYM-US-CBL-0051-1000

Insertion loss	≤ 8.65 dB at 67 GHz
Length tolerance	±10 mm

Values are typical or maximum figures stated in the manufacturer's datasheet, not a Kymopsis lab report. Ask us for the manufacturer's test data where one exists.

Passive RF component for laboratory, development and integration use. It does not transmit on its own and carries no FCC, CE or other equipment certification claim.

Kymopsis · kymopsis.com · support@kymopsis.com. Specifications may change without notice. Custom lengths, connectors and bands: kymopsis.com/b2b/