# 2.4mm Female Connector End Launch Suit for PCB Thickness 0.9mm, DC–50 GHz

Coaxial connector · DC–50 GHz · 2.4mm female



## Overview

2.4mm Female Connector End Launch Suit for PCB Thickness 0.9mm, rated DC–50 GHz. All figures are the maker's datasheet values. Ships from US stock.

## Applications

- Building custom cable assemblies
- Panel, PCB or module RF interfaces

## Specifications

| | |
|---|---|
| **Frequency** | DC–50 GHz |
| **Impedance** | 50 Ω |
| **Connector** | 2.4 mm female |
| **VSWR** | 1.25 |
| **Insertion loss** | ≤ 0.05 × √f(GHz) |
| **Termination type** | PCB |
| **Body style** | Straight |
| **Mount method** | End Launch |
| **Body material** | Brass |
| **Body plating** | Gold |
| **Weight** | 2 g |
| **Mating cycles, min** | ≥500 |
| **Operating temperature** | −55 °C to +165 °C |
| **RoHS** | Yes |

Values are typical or maximum figures stated in the manufacturer's datasheet, not a Kymopsis lab report. Ask us for the manufacturer's test data where one exists.

Passive RF component for laboratory, development and integration use. It does not transmit on its own and carries no FCC, CE or other equipment certification claim.

Kymopsis · kymopsis.com · support@kymopsis.com. Specifications may change without notice. Custom lengths, connectors and bands: kymopsis.com/b2b/