GPPO (Mini-SMP) Female Connector for .086" Series Cables, DC–65 GHz

Coaxial connector · DC–65 GHz · GPPO female



Overview

GPPO (Mini-SMP) Female Connector for .086" Series Cables, rated DC–65 GHz. All figures are the maker's datasheet values. Ships from US stock.

Applications

- Building custom cable assemblies
- Panel, PCB or module RF interfaces

Specifications

Frequency	DC–65 GHz
Impedance	50 Ω
Connector	GPPO female
VSWR	1.1 to 26.5 GHz, 1.32 to 50 GHz, 1.5 to 65 GHz
Insertion loss	≤ 0.1 × √f(GHz)
Termination type	Coax
Body style	Straight
Body material	Beryllium Copper
Body plating	Gold
Weight	0.2 g
Mating cycles, min	≥500
Operating temperature	−55 °C to +165 °C
RoHS	Yes

Values are typical or maximum figures stated in the manufacturer's datasheet, not a Kymopsis lab report. Ask us for the manufacturer's test data where one exists.

Passive RF component for laboratory, development and integration use. It does not transmit on its own and carries no FCC, CE or other equipment certification claim.

Kymopsis · kymopsis.com · support@kymopsis.com. Specifications may change without notice. Custom lengths, connectors and bands: kymopsis.com/b2b/