GPPO (Mini-SMP) Male Connector End Launch Length 6.8mm, DC–40 GHz

Coaxial connector · DC–40 GHz · GPPO male



Overview

GPPO (Mini-SMP) Male Connector End Launch Length 6.8mm, rated DC–40 GHz. All figures are the maker's datasheet values. Ships from US stock.

Applications

- Building custom cable assemblies
- Panel, PCB or module RF interfaces

Specifications

Frequency	DC–40 GHz
Impedance	50 Ω
Connector	GPPO male
VSWR	1.5 to 26.5 GHz
Insertion loss	≤ 0.1 × √f(GHz)
Termination type	PCB
Body style	Straight
Body material	Brass
Body plating	Gold
Weight	0.33 g
Mating cycles, min	≥500
Operating temperature	−55 °C to +165 °C
RoHS	Yes

Values are typical or maximum figures stated in the manufacturer's datasheet, not a Kymopsis lab report. Ask us for the manufacturer's test data where one exists.

Passive RF component for laboratory, development and integration use. It does not transmit on its own and carries no FCC, CE or other equipment certification claim.

Kymopsis · kymopsis.com · support@kymopsis.com. Specifications may change without notice. Custom lengths, connectors and bands: kymopsis.com/b2b/