N Male to SMA Male Cable Assembly, 311A Series Low-Loss Phase-Stable Microwave Coaxial Cable, OD 7.9mm, DC–18 GHz

Coaxial cable assembly · DC–18 GHz · N / SMA male / male · 8 lengths, 500 mm to 5000 mm



Overview

N Male to SMA Male Cable Assembly, rated DC–18 GHz. Available in 8 lengths from 500 mm to 5000 mm, listed below. All figures are the maker's datasheet values. Ships from US stock.

Applications

- Connecting instruments, modules and antennas
- Test-bench and lab wiring
- Integration in RF and radar test setups

Specifications

Frequency	DC–18 GHz
Impedance	50 Ω
Connector 1	N male straight; stainless steel, passivated
Connector 2	SMA male straight; stainless steel, passivated
VSWR	<1.35
RF leakage	100 dB
Cable type	311A Low Loss Flexible Cable
Cable outer diameter	7.9 mm
Mating cycles, min	≥500
Operating temperature	−40 °C to +125 °C
RoHS	Yes
Inner conductor material	Silver Plated Copper (SPC)
Dielectric material	LD-PTFE

Jacket material	FEP
Cable color	Turquoise
Minimum bend radius	31.75 mm
Capacitance (pF/m)	80
Velocity of propagation	82%
Shielding effectiveness	<-100 dB

Options (Length)

500 mm · SKU KYM-US-CBL-0335-500

800 mm · SKU KYM-US-CBL-0335-800

1000 mm · SKU KYM-US-CBL-0335-1000

1200 mm · SKU KYM-US-CBL-0335-1200

1500 mm · SKU KYM-US-CBL-0335-1500

2000 mm · SKU KYM-US-CBL-0335-2000

3000 mm · SKU KYM-US-CBL-0335-3000

5000 mm · SKU KYM-US-CBL-0335-5000

Values are typical or maximum figures stated in the manufacturer's datasheet, not a Kymopsis lab report. Ask us for the manufacturer's test data where one exists.

Passive RF component for laboratory, development and integration use. It does not transmit on its own and carries no FCC, CE or other equipment certification claim.

Kymopsis · kymopsis.com · support@kymopsis.com. Specifications may change without notice. Custom lengths, connectors and bands: kymopsis.com/b2b/