# SMA Male Reverse Polarity for .141" Series Cable, DC–18 GHz

Coaxial connector · DC–18 GHz · SMA male



## Overview

SMA Male Reverse Polarity for .141" Series Cable, rated DC–18 GHz. All figures are the maker's datasheet values. Ships from US stock.

## Applications

- Building custom cable assemblies
- Panel, PCB or module RF interfaces

## Specifications

| | |
|---|---|
| **Frequency** | DC–18 GHz |
| **Impedance** | 50 Ω |
| **Connector** | SMA male |
| **VSWR** | 1.35 |
| **Insertion loss** | ≤ 0.10 × √f(GHz) |
| **Termination type** | Coax |
| **Body style** | Straight |
| **Body material** | Stainless Steel |
| **Body plating** | Passivated |
| **Mating cycles, min** | ≥500 |
| **Operating temperature** | −40 °C to +125 °C |
| **RoHS** | Yes |

Values are typical or maximum figures stated in the manufacturer's datasheet, not a Kymopsis lab report. Ask us for the manufacturer's test data where one exists.

Passive RF component for laboratory, development and integration use. It does not transmit on its own and carries no FCC, CE or other equipment certification claim.

Kymopsis · kymopsis.com · support@kymopsis.com. Specifications may change without notice. Custom lengths, connectors and bands: kymopsis.com/b2b/